

MA 235 F Datasheet


Table Bases







Logistic Information



SKU/box	Width (cm)	Depth (cm)	Height (cm)	Net Weight (~ kg)	Gross Weight (~ kg)	CBM (m³/box)	20FT DC (SKU)	40FT DC (SKU)	TIR (SKU)
35 SKU/palette	115,0	125,0	125,0	3,2	3,2	1,797	420	840	1.155

Material

- Aluminum high pressure die casting, legs are extruded aluminum profile

Recyclable product

Technical Information

- Outdoor and indoor
- Corrosion resistance
- Shipped assembled
- Light weight
- Dimensional stability
- Folding mechanism

Color Options

White | Black | Others

Coating

- Electrostatic powder coating
- Environmentally friendly surface treatment process provides high corrosion resistance
- Industrial product formulated especially for decoration and protection of metal companents for both outdoor and indoor use. It offers good weathering resistance, good mechanical properties, and a good blance of coating properties.

Certifications

- The powder coating complies with the European Directives "Restriction of the use of certain hazardous substances" 2011/65/EU and 2015/863/EU (RoHS)
- Classification A2 (non flammable) of reaction to fire in accordance with NF EN 13501-1:2018

MH45216 (Fr)

Approvals UL 1332

Maintenance

It is recommended to clean the products regularly especially in humid or marine climate locations to keep them in good condition for a long time. Clean the surfaces using a soft cloth with water or mild detergents. Prolonged and continuous exposure to intense UV radiation from sunlight or very low temperatures can negatively affect the coating therefore to keep products in sheltered places during non-use periods is strongly recommended.

Astor Aluminum
Barbaros Mah. Morsümbül Sk. No:5 D:305 Deluxia Palace
Ataşehir/ İSTANBUL

T: +90 (216) 510 4525
E-mail: info@astoral.com
https://www.astoral.com